

Introduction to XSLT

Version 1.1
July 2012

nikos dimitrakas



Table of contents

1	INTRODUCTION	3
1.1	XSLT	3
1.2	PREREQUISITES.....	3
1.3	STRUCTURE	3
2	SAMPLE DATA	4
3	XSLT	6
4	EXAMPLES.....	7
4.1	HELLO WORLD	7
4.1.1	XML	8
4.1.2	html	10
4.2	SIMPLE ITERATION.....	11
4.3	MULTIPLE TEMPLATES.....	13
4.4	ELIMINATING DUPLICATES.....	16
4.5	MULTIPLE SOURCES.....	18
4.6	CONDITIONALS	20
4.7	DEFAULT VALUES	21
4.8	ATTRIBUTE VALUE TEMPLATES	22
5	EPILOGUE.....	24

1 Introduction

This compendium gives an introduction to XSLT and how to use some of its most common features. All the XSLT features described in the examples later on are part of XSLT 1. Some additional features were introduced in XSLT 2, but since this compendium relies on products that only support XSLT 1, they will not be covered.

The latest version of this compendium is available at <http://coursematerial.nikosdimitrakas.com/xslt/> where all other relevant files can also be found.

1.1 XSLT

XSLT (or XSL Transformations) is a language that can be used to transform XML data from one structure to another. The result may be XML, but it doesn't have to be. A popular output format is html.

XSLT 1 relies on XPath 1, while XSLT 2 relies on XPath 2. Consequently, XSLT 2 is far more powerful and flexible. Unfortunately the major web browsers only support XSLT 1, so since these web browsers will serve as the execution environment for the examples in this compendium, all examples are in XSLT 1. Should you have an execution environment that supports XSLT 2, you could make use of the few new elements defined in XSLT 2 and the extended syntax and function library of XPath 2.

1.2 Prerequisites

It is highly recommended that the reader has a good understanding of XML as well as some knowledge of html and basic programming concepts like loops, conditionals, variables, etc. All the examples can be executed in any major web browser, so having a computer available while reading this compendium is recommended. Since XSLT relies heavily on XPath, prior familiarity with XPath and even XQuery is a plus.

1.3 Structure

In the next chapter we will look at the sample data used for all the examples. In chapter 0 we will take a look at different ways to connect XSLT files to XML files. Then in chapter 0, we will go through several examples using the sample data.

2 Sample Data

In this chapter we will take a look at the XML data that we will use in all the examples to follow. We will use one XML document with information about books and one XML document with information about publishers. The two XML documents are available in the files books.xml and publishers.xml and they are accompanied by books.dtd and publishers.dtd which describe the structure of the two documents. The two DTDs are presented below.

Books.dtd:

```
<!ELEMENT Books (Book+)>
<!ELEMENT Book (Author+,Edition+)>
<!ATTLIST Book Title CDATA #REQUIRED
  OriginalLanguage CDATA #REQUIRED
  Genre CDATA "N/A">
<!ELEMENT Edition (Translation*)>
<!ATTLIST Edition Year CDATA #REQUIRED
  Price CDATA #REQUIRED>
<!ELEMENT Translation EMPTY>
<!ATTLIST Translation Language CDATA #REQUIRED
  Publisher CDATA "N/A"
  Price CDATA #REQUIRED>
<!ELEMENT Author EMPTY>
<!ATTLIST Author Name CDATA #REQUIRED
  Email CDATA #REQUIRED
  YearOfBirth CDATA #REQUIRED
  Country CDATA #REQUIRED>
```

The definition in books.dtd can be graphically represented according to the following figure.




Figure 1 Graphical representation of books.dtd

Publishers.dtd:

```
<!ELEMENT Publishers (Publisher+)>
<!ELEMENT Publisher (Address)>
<!ATTLIST Publisher Name CDATA #REQUIRED>
<!ELEMENT Address (Street, City, PostalCode, Country)>
<!ELEMENT Street (#PCDATA)>
<!ELEMENT City (#PCDATA)>
<!ELEMENT PostalCode (#PCDATA)>
<!ELEMENT Country (#PCDATA)>
```

The definition in publishers.dtd can be graphically represented according to the following figure.




Figure 2 Graphical representation of publishers.dtd

DTDs can unfortunately not express certain details like data types, unique constraints and other complex business rules. For the remainder of this compendium we will consider the following rules to also be valid in the two XML documents:

- Every book has a unique title
- Every author has a unique name and a unique e-mail
- Two editions of the same book may not have the same year
- Two translations of the same edition may not have the same language
- Every publisher has a unique name
- The value of the attribute Publisher in the element Translation always corresponds to the name of a publisher
- The attributes Price, Year and YearOfBirth allow only positive integers as their value

3 XSLT

An XSLT file is usually a file with the extension .xsl. Such a file contains all the transformation rules to be applied to an XML file. One way to link the two files to each other is to insert a reference to the XSLT file in the XML file. This is done with the following processing instruction just before the root element of the XML document:

```
<?xml-stylesheet type="text/xsl" href="filename.xsl"?>
```

Where "filename.xsl" is of course the name of the XSLT file. This reference can be relative to the location of the XML file or an absolute filename reference.

This method would of course imply that you can only have one XSLT file associated with each XML file, which would be quite inflexible. The linking of the XSLT file could of course be done dynamically for example if your XML file is generated by a program.

Another possible solution is to let the XSLT file reference the XML file it wants to use. This can be done by using the XPath function "document". This gives us the possibility to also have an XSLT file that works with two or more sources. The disadvantage is, of course, that the XSLT files cannot be reused for different XML files. So choose your solution wisely!

For the examples in the next chapter, we will use any XSLT capable web browser as our execution environment. These browsers will apply the referenced XSLT file when an XML file (with such a reference) is opened. Should we try to open an XSLT file directly in a browser, then the XSLT file would be considered to be the opened XML file (since XSLT files are also XML files) and it would just be displayed. So in order to have the content of the XSLT file executed and not just displayed, we need to always open an XML file with a reference to the XSLT file. So we have the following two options (which correspond to the alternatives discussed earlier):

1. Add a reference to the XSLT file in the XML file that contains the data and open it in a browser.
2. Write an XSLT file that uses the "document" function in order to access the XML file with the data, and then use another XML file with just a reference to the XSLT file and an empty root element. Such a file could look like this:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<?xml-stylesheet type="text/xsl" href="filename.xsl"?>
<root/>
```

4 Examples

In this chapter we will go through several examples in order to test some of the most common declarations and instructions that are part of XSLT. In most examples we will only use one XML file as the data source.

4.1 *Hello World*

Let's start with a very basic example just to check that everything works correctly. The goal is to show the text "Hello World" as the output if there is a root element. Our XSLT file (named hello.xsl) could have the following content:


```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
<xsl:output method="text"/>
<xsl:template match="/">
  <xsl:text>Hello World</xsl:text>
</xsl:template>
</xsl:transform>
```

Then we need an XML file (let's call it hello.xml) with a reference to the XSLT file. The content of the XML file should be the following:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<?xml-stylesheet type="text/xsl" href="hello.xsl"?>
<root/>
```

By opening the XML file in a web browser, the XSLT file will be called and the contained templates will be applied if they match. Our XSLT file has only one template and it matches the root element of the XML document. The content of the template element will thus start constructing the output. The element `xsl:output` is a declaration that informs the executing environment that the result will be of a certain type, in our case plain text. Other common output methods are `xml` and `html`. The element `xsl:text` is an instruction that creates text in the output.

The result would look like the following screenshots from 6 major web browsers¹:



Since all the elements in the XSLT file belong to the same namespace, it would be correct to rewrite the file's content as the following:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<transform version="1.0" xmlns="http://www.w3.org/1999/XSL/Transform">
<output method="text"/>
<template match="/">
  <text>Hello World</text>
</template>
</transform>
```


4.1.1 XML

We may of course want the output to be XML instead of plain text. In that case we can change the output method to xml and construct the desired XML structure inside the template element:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
<xsl:output method="xml" />
<xsl:template match="/">
  <root><Hello>World</Hello></root>
</xsl:template>
</xsl:transform>
```

¹ For Chrome to work with local files, it must be started with the following command line parameter `--allow-file-access-from-files`. This is due to some security design decision by Chrome developers.


The result may look different in each browser depending on the setting for displaying XML. Here are two examples:



In the example above we created our elements directly, but we could instead use XSLT instructions for that. In the example below we create the elements "root" and "Hello" and we create an attribute "to" with "World" as its value:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
<xsl:output method="xml" />
<xsl:template match="/">
  <xsl:element name="root">
    <xsl:element name="Hello">
      <xsl:attribute name="to">World</xsl:attribute>
    </xsl:element>
  </xsl:element>
</xsl:template>
</xsl:transform>
```


The result would be the following:



The main components in an XML document are elements and attributes, but we may also want to create comments or processing instructions. The XSLT instructions "comment" and "processing-instruction" can help us with that. Here is a simple example:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:output method="xml" />
  <xsl:template match="/">
    <xsl:processing-instruction name="xml-hello">to="World"</xsl:processing-instruction>
    <xsl:comment>Just an example for XSLT instructions</xsl:comment>
    <xsl:element name="root">
      </xsl:element>
    </xsl:template>
  </xsl:transform>
```

And the result would look like this:




4.1.2 html

Another popular output method is html. Since we are using web browsers as our execution environment and display facility, it is only reasonable to use html for the output. The web browsers will automatically render the result as html. Here is an example:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:output method="html" />
  <xsl:template match="/">
    <html>
      <head>
        <title>XSLT says hello</title>
      </head>
      <body>
        <h1>Hello World</h1>
      </body>
    </html>
  </xsl:template>
</xsl:transform>
```

The result is a very simple html page that a browser could render like this:



We could of course use the XSLT instruction "element" in order to create the elements "html", "head", "title", "body" and "h1" but the result would be the same.

4.2 Simple iteration

It's now time to use some XML input data in the output. We can start by creating an XSLT file (booktitles.xsl) with the following content:


```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:template match="/">
    <html>
      <head><title>Book titles</title></head>
      <body>
        <h1>Books</h1>
        <xsl:for-each select="document('books.xml')//Book">
          <p><xsl:value-of select="@Title"/></p>
        </xsl:for-each>
      </body>
    </html>
  </xsl:template>
</xsl:transform>
```

The template that matches the root of the calling document will create the html content of the output. The new thing here is the XSLT instruction "for-each", where we retrieve a sequence of Book elements from the XML file "books.xml". For each such node, we construct an html paragraph with the current book's title (the value of the Title attribute node inside the Book element node). The reference to @Title is relative to the current book in the for-each loop.

Now we need an XML file to call the XSLT file. We can create an XML file (booktitles.xml) with the following content:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<?xml-stylesheet type="text/xsl" href="booktitles.xsl"?>
<root/>
```

When we open this file in a browser, the browser will use the XSLT in booktitles.xsl in order to style the opened file. The XSLT will in turn open the XML file books.xml (which contains our sample data) and create one paragraph for each Book element found there. The result will look like this:



It is of course possible to add the reference to the XSLT file directly in the XML file books.xml. In that case the XSLT file does not have to use the XPath function "document", since it is already in that context. We can create a new version of the XSLT file as booktitles2.xsl with the content slightly modified:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:template match="/">
    <html>
      <head><title>Book titles</title></head>
      <body>
        <h1>Books</h1>
        <xsl:for-each select="//Book">
          <p><xsl:value-of select="@Title"/></p>
        </xsl:for-each>
      </body>
    </html>
  </xsl:template>
</xsl:transform>
```

Then we just add the following processing instruction to books.xml just before the opening tag <Books>:

```
<?xml-stylesheet type="text/xsl" href="booktitles2.xsl"?>
```

Now if we open the XML file books.xml in a browser we will get the same result as before.

4.3 Multiple templates

Another way to work with XSLT is to use templates recursively instead of using for-each loops. So let's try to create the same result as in the previous example by using templates instead of loops. We can create a new XSLT file (booktitles3.xsl) with the following content:


```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:template match="/">
    <html>
      <head><title>Book titles</title></head>
      <body>
        <h1>Books</h1>
        <xsl:apply-templates select="document('books.xml')//Book" />
      </body>
    </html>
  </xsl:template>
  <xsl:template match="Book">
    <p><xsl:value-of select="@Title"/></p>
  </xsl:template>
</xsl:transform>
```

This XSLT file has two templates: one matching the root of the document, and one that matches Book elements. As usual, the first template will serve as the initiator of the process. It will start creating the html output and after the h1 element, it will ask for all the relevant templates to be applied to the selection. Since the selection is a sequence of Book element nodes, the relevant templates will be applied to each node in the sequence. The only relevant template for such nodes is our second template, which creates an html paragraph.

We can test our XSLT by creating a new XML file (booktitles3.xml) to call the XSLT. Its content should be the following:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<?xml-stylesheet type="text/xsl" href="booktitles3.xsl"?>
<root/>
```

And the result will once again be the same as before:




We can now expand this solution to also show the names of all the authors as an unordered list after each title. We can create a new XSLT file (booktitlesauthors.xml) with the following content:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:template match="/">
    <html>
      <head><title>Book titles</title></head>
      <body>
        <h1>Books</h1>
        <xsl:apply-templates select="document('books.xml')//Book" />
      </body>
    </html>
  </xsl:template>
  <xsl:template match="Book">
    <p>
      <xsl:value-of select="@Title"/>
      <ul><xsl:apply-templates select="Author" /></ul>
    </p>
  </xsl:template>
  <xsl:template match="Author">
    <li><xsl:value-of select="@Name"/></li>
  </xsl:template>
</xsl:transform>
```

We have added a third template which matches Author elements and creates html list items. We have also modified the second template so that it not only creates a paragraph with the book title, but it also places, in the paragraph, an html unordered list whose content is the result of applying all relevant templates to the node sequence returned by the XPath expression "Author" (which of course is relative to the current Book element).

Using a new XML file (booktitlesauthors.xml) with a reference to the new XSLT file, we can get the result:



The same result can of course be achieved by using nested for-each instructions like this:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:template match="/">
    <html>
      <head><title>Book titles</title></head>
      <body>
        <h1>Books</h1>
        <xsl:for-each select="document('books.xml')//Book">
          <p>
            <xsl:value-of select="@Title"/>
            <ul>
              <xsl:for-each select="Author">
                <li><xsl:value-of select="@Name"/></li>
              </xsl:for-each>
            </ul>
          </p>
        </xsl:for-each>
      </body>
    </html>
  </xsl:template>
</xsl:transform>
```

4.4 *Eliminating duplicates*


In XPath 2 we can use the function "distinct-values" in order to eliminate duplicate values. In XPath 1 we need to do this in a different way. We can use the "preceding" axis and check that no previous value is the same as the current one, thus only keeping the first occurrence of each value. We may want to create a list of all the authors with a sublist with each author's books. We could do this by finding all the authors (without duplicates) and then looking for books for the current author in a loop:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:template match="/">
    <html>
      <head><title>Authors</title></head>
      <body>
        <h1>Authors</h1>
        <xsl:variable name="doc" select="document('books.xml')"/>
        <xsl:for-each select="$doc//Author[not(@Name = preceding::Author/@Name)]">
          <xsl:sort select="@Name" order="descending"/>
          <xsl:variable name="n" select="@Name"/>
          <ul>
            <li>
              <xsl:value-of select="@Name"/>
              <ul>
                <xsl:for-each select="$doc//Book[Author/@Name = $n]">
                  <li><xsl:value-of select="@Title"/></li>
                </xsl:for-each>
              </ul>
            </li>
          </ul>
        </xsl:for-each>
      </body>
    </html>
  </xsl:template>
</xsl:transform>
```

Here we use a few new features. The first one is the XSLT instruction "variable". This is a simple instruction for assigning values to variables. The value is the result of the evaluation of the XPath expression specified in the select attribute. The variable can later be referenced in any XPath expression (by using the standard XPath variable mechanism: adding a dollar sign in front of the variable name). The second one is the "sort" instruction², which allows us to order the result of any loop. In this example we order the result according to the author names in descending order.

² Technically xsl:sort is not classified as an instruction in the specification. It is instead a support subelement to other instructions.


The result would look like this:



We may want to show the number of books each author has written, instead of showing the titles. And we may want to put the result in an html table instead of a plain list. For that we can use the following XSLT:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:template match="/">
    <xsl:variable name="doc" select="document('books.xml')"/>
    <html>
      <head><title>Authors</title></head>
      <body>
        <table border="1">
          <tr>
            <th>Author name</th>
            <th>Number of books</th>
          </tr>
          <xsl:for-each select="$doc//Author[not(@Name = preceding::Author/@Name)]">
            <xsl:sort select="@Name" order="descending" />
            <xsl:variable name="n" select="@Name"/>
            <tr>
              <td><xsl:value-of select="@Name"/></td>
              <td><xsl:value-of select="count($doc//Book[Author/@Name = $n])"/></td>
            </tr>
          </xsl:for-each>
        </table>
      </body>
    </html>
  </xsl:template>
</xsl:transform>
```

Here we use the XPath function "count", which returns the number of nodes (or values) in the sequence provided as the function's parameter. The result looks like this:



Author name	Number of books
Sam Davis	2
Pierre Zargone	1
Peter Feldon	1
Peter de Jonge	1
Mimi Pappas	1
Meg Gilmand	1
Marty Faust	1
Marie Franksson	2
Linda Evans	1
Lilian Carrera	1

4.5 Multiple sources

Sometimes the data we need may be available in different sources. As described earlier, our data is in two files: books.xml and publishers.xml. We may need to combine these two files, for example if we want to find books published by Swedish publishers. We can start by finding all the Swedish publishers in publishers.xml and then use the result in order to find books in books.xml that have been published by the right publishers. It is actually the translations of the different editions that have a publisher, so that's where we are going to look. The following XSLT does that and returns the titles of the right books.

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:variable name="books" select="document('books.xml')"/>
  <xsl:variable name="publishers" select="document('publishers.xml')"/>
  <xsl:template match="/">
    <html>
      <head><title>Books</title></head>
      <body>
        <h1>Books with translations published by Swedish publishers</h1>
        <ol>
          <xsl:apply-templates select="$publishers//Publisher[Address/Country = 'Sweden']"/>
        </ol>
      </body>
    </html>
  </xsl:template>
```


```
<xsl:template match="Publisher">
  <xsl:variable name="p" select="@Name" />
  <li>
    <xsl:value-of select="$p"/>
    <ul>
      <xsl:apply-templates select="$books//Book[Edition/Translation/@Publisher = $p]"/>
    </ul>
  </li>
</xsl:template>
<xsl:template match="Book">
  <li>
    <xsl:value-of select="@Title"/>
  </li>
</xsl:template>
</xsl:transform>
```

As usual, the first template is used to initiate the result and it retrieves a sequence of Publisher element nodes (the publishers from Sweden) and applies all the relevant templates. The second template takes care of the Publisher elements and creates one list item for each. It also retrieves (from the other file) the relevant books and applies the relevant templates on them. The third template creates a list item for each Book element. The result looks like this:



4.6 Conditionals

XSLT, just as many other languages, has an "if" instruction and a "choose" instruction. The "if" instruction does not support an "else" clause, while the "choose" instruction can have several "when" clauses and possibly an "otherwise" clause. We could use these instructions when we want to vary the output based on certain conditions. Let's create an output that shows all the books and highlights the books that are available in Swedish, with some additional information about the number of translations. We want the output to look like this:



We can achieve the desired output with the following XSLT:

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:variable name="books" select="document('books.xml')"/>
  <xsl:template match="/">
    <html>
      <head><title>Books</title></head>
      <body>
        <xsl:apply-templates select="$books//Book"/>
      </body>
    </html>
  </xsl:template>
```

```

<xsl:template match="Book">
  <p>
    <xsl:value-of select="@Title"/>
    <xsl:if test="Edition/Translation/@Language = 'Swedish'">
      <br /> - Available in Swedish
    </xsl:if>
    <xsl:choose>
      <xsl:when test="count(Edition/Translation)=0">
        <br /> - No translations
      </xsl:when>
      <xsl:when test="count(Edition/Translation)=1">
        <br /> - One translation
      </xsl:when>
      <xsl:otherwise>
        <br /> - Many translations
      </xsl:otherwise>
    </xsl:choose>
  </p>
</xsl:template>
</xsl:transform>

```

4.7 Default values


One interesting aspect of XML is that the associated DTD or XML Schema may provide default values for attributes that may be missing in the XML document. In our sample data we have an attribute Genre that may be missing, and in that case the default value is "N/A". XSLT can use the information in the DTD and return the default value instead of nothing. We can try this by selecting all the book titles and genres with this simple XSLT (file genres.xml):

```

<?xml version="1.0" encoding="ISO-8859-1"?>
<xsl:transform version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
  <xsl:template match="/">
    <html>
      <head><title>Book titles and genres</title></head>
      <body>
        <h1>Books</h1>
        <xsl:for-each select="document('books.xml')//Book">
          <p><xsl:value-of select="@Title"/>, Genre: <xsl:value-of select="@Genre"/></p>
        </xsl:for-each>
      </body>
    </html>
  </xsl:template>
</xsl:transform>

```

Unfortunately, not all browsers implement the default lookup, so the result may differ like this:



4.8 Attribute value templates

When creating output, there are two main ways of creating nodes (elements, attributes, etc.). The one way is to use node creation instructions (like `xsl:element`, `xsl:attribute`, `xsl:text`, `xsl:comment`, etc). The other way is to write directly the textual representation of the nodes (as we have done in the examples earlier in this chapter). Let's look at a simple example with both these methods. We can use the XML document with the publishers and produce the following structure:

```
<Publishers>
  <Publisher Name="" Country="" />
  <Publisher Name="" Country="" />
</Publishers>
```

The first solution is with node creation instructions:


```
<xsl:transform xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="1.0">
  <xsl:output method="xml"/>
  <xsl:variable name="publishers" select="document('publishers.xml')"/>
  <xsl:template match="/">
    <xsl:element name="Publishers">
      <xsl:for-each select="$publishers//Publisher">
        <xsl:element name="Publisher">
          <xsl:copy-of select="@Name"/>
          <xsl:attribute name="Country">
            <xsl:value-of select="."/Country"/>
          </xsl:attribute>
        </xsl:element>
      </xsl:for-each>
    </xsl:element>
  </xsl:template>
</xsl:transform>
```

The second solution is to just type the xml content directly:

```
<xsl:transform xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="1.0">
  <xsl:output method="xml"/>
  <xsl:variable name="publishers" select="document('publishers.xml')"/>
  <xsl:template match="/">
    <Publishers>
      <xsl:for-each select="$publishers//Publisher">
        <Publisher Name="{@Name}" Country="{./Country}" />
      </xsl:for-each>
    </Publishers>
  </xsl:template>
</xsl:transform>
```

Here we have to use attribute value templates like {@Name}. It is not possible to use xsl:value-of since that would cause the XSLT file to not be well-formed.

Both solutions produce the same result:



Attribute value templates can of course be combined with node creation instructions in order to produce element names or attribute names that are dynamic. We could for example use the country as the element name instead of "Publisher". Try it!

5 Epilogue

There are many more details about XSLT that we could discuss, but the goal of this compendium is only to serve as a "Getting started" introduction. There are many good resources about XSLT that could be of value if you want to become an expert. First and foremost, the XSLT specification. In many cases the specification may be too formal and hard to understand. So, books like "The XML 1.1 Bible" could serve you well.

In the examples that generate html as output, we used only very basic html components. It is of course possible to use the full power of html with images, css, javascript, etc. But the focus of the examples has been on the XSLT and not on the graphical design of the output.

I hope you have found this introduction educational and fun. Do not hesitate to send comments and suggestions that may help improve the next version of the compendium!

The Author

nikos dimitrakas